



Halogen non-reflector

7158 150W G6.35 24V 1CT/10X10F

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.


Product data

General Information		Voltage (Nom)	
Cap-Base	G6.35 [G6.35]	24 V	
Philips Code	7158	Mechanical and Housing	
ANSI Code	FCS	Bulb Material	Quartz-UV Open
LIF Code	A1/216	Filament Shape	Flat
Operating Position	S90 [Standing +/-90D or Base Down (BDH)]	Filament Dimensions WxH	5.8x2.9
Main Application	Projection	Luminaire Design Requirements	
Life to 50% Failures (Nom)	50 h	Bulb Temperature (Max)	900 °C
Light Technical		Pinch Temperature (Max)	400 °C
Luminous Flux (Rated) (Nom)	5200 lm	Product Data	
Correlated Color Temperature (Nom)	3450 K	Full product code	871150040983650
Color Rendering Index (Nom)	100	Order product name	7158 150W G6.35 24V 1CT/10X10F
Operating and Electrical		EAN/UPC - Product	8711500409836
Power (Rated) (Nom)	150 W	Order code	923870520503
		Numerator - Quantity Per Pack	1

Halogen non-reflector

Numerator - Packs per outer box	100
Material Nr. (12NC)	923870520503
Net Weight (Piece)	0.004 kg

Dimensional drawing



7158 150W G6.35 24V

Product	D (max)	L (min)	L (max)	L	P (max)	P	P (min)	C (max)
7158 150W	11.5 mm	31.5 mm	32.25	32	1.05 mm	1 mm	0.95 mm	50 mm
G6.35 24V			mm	mm				
1CT/10X10F								

